

3 ph – Motor

POS.1

Type		<i>LA100L-8/4A</i>
Leistung / Rated output	(kW)	<i>0,6/2,7 // 0,8/3,1</i>
Betriebsart / Operating mode	S	<i>1</i>
Spannung / Voltage	(V)	<i>380-420 // 440-480</i>
Schaltung / Circuit		<i>Y / YY // Y/YY</i>
Frequenz / Frequency	(Hz)	<i>50 // 60</i>
Drehzahl / Rated speed	(1/min)	<i>685/1390 // 830/1700</i>
Wärmeklasse / Insulating class		<i>F</i>
Kaltleiterfühler / Thermistor protection		<i>--</i>
Thermof. (Öffner) / Thermal protect.(NC)		<i>--</i>
Bauform / Type of construction		<i>B5/V1</i>
Flansch / Flange		<i>Ø 250mm</i>
Welle / Shaft		<i>Ø 24*40mm</i>
Schutzart / Degree of protection	IP	<i>54</i>
Kühlung / Cooling		<i>eigen</i>
Bremse / Brake	(Nm)	<i>--</i>
Spannung / DC Voltage	= (V)	<i>--</i>
Gleichrichter / Rectifier		<i>--</i>
Wechselspannung / AC Voltage	~ (V)	<i>--</i>